



IKALL

MODULAR IKALL ENTRANCE PANEL



Clean, attractive lines and modular elements guaranteeing optimal results by offering simple configuration, style and reliability. Ikall is available as a digital version featuring Sensitive Touch technology or as an analogue version, with large nameplates that are easy to remove and in a wide variety of colour combinations. Large display, name uploading via USB port, audio-visual indications by means of pictograms with LED backlighting, audio messages, programmable welcome message, 16 available languages, 'Screen Saver' function. The product is certified as IP54.



IKALL

MODULAR IKALL ENTRANCE PANEL

GENERAL DATA

Type	Modular
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.4682HC, Art.1621, Art.1622, Art.1622VC, Art.4680C, Art.4681, 4680CW
Audio/video Simplebus 2 with power supply art. 4888CU	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio/video Simplebus 1	Yes
Audio Simplebus 1	Yes
ViP	Yes

HARDWARE FEATURES

Call type	Push-buttons, Digital
Type of buttons	Mechanical
Number of push-buttons (n°)	100
Backlight color	Blue, White, Off

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Operating temperature (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3332

IKALL SERIES AUDIO INDUCTION LOOP MODULE

Ikall series module with audio induction loop which allows hard-of-hearing users to listen to the audio conversation on the external unit via their own hearing aid device (with T switch). Module for use in conjunction with the 2-wire audio/video unit art. 4681BM or the ViP audio/video module art. 4682BM. Dimensions: 112x89.5x38 mm



4682HD

HD AUDIO/VIDEO UNIT IP (VIP)

ViP system audio-video unit with terminal block, complete with colour camera. Resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). IR led camera lighting. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electrets microphone; loudspeaker volume can be adjusted from the front. Programmable audio visual functions for users with disabilities. Standard POE audio-video unit, but if necessary 33 VDC power supply can be used the power supply unit art. 1595. Compatible with H.264 video format. Dimensions: 102x55x38 mm.



3348B

ELECTRONIC KEY MODULE, IKALL SERIES

Digital electronic key module with LED keypad backlighting. Blue, white and off lighting options. When a number with between 1 and 8 digits is entered on the keypad, two relays (10A) are activated, allowing the operation of electric door locks or other devices. Dimensions 112x89.5x40 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES

**3360B****2-WIRE AND VIP CALL MODULE. IKALL SERIES**

Digital call module with 128x64 dot graphic LCD display and keypad with 21 buttons backlit with blue LEDs. Also functions as an electronic key code. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. For the SBC system (factory setting), the electronic name directory saves up to 3500 user names and 6000 lock-release passwords. Users and settings are simple to program using PC software art. 1249B (included, with USB connection cable) via a USB or RS485 port, or locally on the digital module itself. Includes the CD-ROM loaded with serial download SW art. 1249B for installation to PC and the USB connection cable. Dimensions: 112x180x40

**1621****Simplebus 2W audio unit with LED, Ikall series**

Speaker unit for 2-wire systems complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



4681

2 WIRES AUDIO/VIDEO UNIT

Colour audio-video unit for 2-wire systems with terminal block complete with directable colour camera with front adjustment, LED camera lighting. Complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. Programmable audiovisual functions for users with disabilities. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



1621VC

2 WIRES IKALL AUDIO UNIT FOR REMOTE CAMERA

Speaker unit for 2-wire systems complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Allows use of external PAL colour cameras. Complete with microprocessor and 8-position dip switch for programming calls to users. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



4682HC

COL.AUD/VID UNIT FOR VIP SYST., IKALL SERIES.H264

Audio-video unit for ViP system including terminal block complete with front-adjustable mini lens colour camera, LED camera lighting. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES




1682HVC IKALL SERIES AUDIO MOD. FOR REM.COL.CAM. VIP. H264

ViP system audio unit with facility for connection of a remote camera with 12Vdc power supply. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. Dimensions: 102x55x38 mm. Compatible with H.264 video format.



1235A NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



1218 NAME TAG SHEETS FOR IKALL ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for single nameplates, 7 sheets for double nameplates and 3 sheet for information modules.



33400K AUDIO FACEPLATE KIT FOR VISUAL INDICATIONS. IKALL SERIES

Black faceplate kit for audio module 1622L. Dimensions: 95x90x7mm.



1682 IKALL VIP AUDIO ONLY SPEAKER

Audio unit for ViP system. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: part. 33400, 33401, 33402. Dimensions: 102x55x38 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



4680CW D&N WIDE COLOUR A/V UNIT. IKALL SERIES SIMPLEBUS

Audio/video unit with terminal block, Simplebus 2 system, complete with colour camera with 2.3 mm lens and IR illumination. Digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and dip-switch with 8 positions for programming calls to users. Programmable audiovisual indications to comply with DDA. 33 VDC power supply via power supply unit part. 1595. On-board electronic lock-release function (3A), plus C-NC-NO 10A relay contacts. Compatible with all Simplebus 2 functions and products. Allows call addressing up to 120000 users. Timed door opening and door open visualization. To add in the audio-video modules with 0, 1 and 2 buttons. Dimensions: 102x55x38 mm.



3311/4AL 4 MODULE SURROUND WITH ANODISED ALUMINIUM FRAME

Made of die-cast aluminum with an anodized aluminum frame ideal for installation in extreme situations such as the marine environment, 3 modules. Dimensions 125x395x37.5mm



3311/3AL 3 MODULE SURROUND WITH ANODISED ALUMINIUM FRAME

Made of die-cast aluminum with an anodized aluminum frame ideal for installation in extreme situations such as the marine environment, 3 modules. Dimensions 125x305x37.5mm



3311/2AL 2 MODULE SURROUND WITH ANODISED ALUMINIUM FRAME

Made of die-cast aluminum with an anodized aluminum frame ideal for installation in extreme situations such as the marine environment, 2 modules. Dimensions 125x215x37.5mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3311/1AL 1 MODULE SURROUND WITH ANODISED ALUMINIUM FRAME

Made of die-cast aluminium with an anodized aluminum frame ideal for installation in extreme situations such as the marine environment, 1 module. Dimensions 125x125x37.5mm



3311/3S IKALL SERIES 3-MODULES HOLDER FRAME, SILVER FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 3 modules. Silver colour. Dimensions 125x305x37,5 mm



3311/2S IKALL SERIES 2-MODULES HOLDER FRAME, SILVER FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 2 modules. Silver colour. Dimensions 125x215x37,5mm



3311/1S IKALL SERIES 1-MODULE HOLDER FRAME, SILVER FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 1 module. Silver colour. Dimensions 125x125x37,5mm



IKALL

MODULAR IKALL ENTRANCE PANEL


ACCESSORIES



4680C

2 WIRES AUDIO/VIDEO UNIT


Simplebus 2 system audio/video unit with terminal block complete with front-adjustable wide-angle 1.3" CCD colour camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audiovisual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



3649/3

45° INCLINATION HOUSING 3 MODULES ENTRANCE PANEL

Housing made of aluminium which allows the Ultra, Powercom, Ikall and Ikall Metal entrance panel to be rotated by 45°. Once fitted to the wall, the housing angles the entrance panel laterally towards the user for easier and practical use. N° modules: 3. Dimensions: 183x354x100 mm.



3649/2

45° INCLINATION HOUSING 2 MODULES ENTRANCE PANEL

Housing made of aluminium which allows the Ultra, Powercom, Ikall and Ikall Metal entrance panel to be rotated by 45°. Once fitted to the wall, the housing angles the entrance panel laterally towards the user for easier and practical use. N° modules: 2. Dimensions: 183x242x100 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3649/1

45° INCLINATION HOUSING 1 MODULE ENTRANCE PANEL

Housing made of aluminium which allows the Ultra, Powercom, Ikall and Ikall Metal entrance panel to be rotated by 45°. Once fitted to the wall, the housing angles the entrance panel laterally towards the user for easier and practical use. N° modules: 1. Dimensions: 183x130x100 mm.



3640/3

COLUMN FOR 3-MODULES ENTRANCE PANEL, HEIGHT 117CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 3 modules. Dimensions 118x117x7,5 cm



3640/2

COLUMN FOR 2-MODULES ENTRANCE PANEL, HEIGHT 117CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 3 modules. Dimensions 118x117x7,5 cm



3640/1

COLUMN FOR 1-MODULE ENTRANCE PANEL, HEIGHT 117CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 1 module. Dimensions 18x117x7.5 cm



3639/3

COLUMN FOR 3-MODULES ENTRANCE PANEL, HEIGHT 170CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 3 modules. Dimensions 118x170x7.5 cm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3639/2

COLUMN FOR 2-MODULES ENTRANCE PANEL, HEIGHT 170CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 2 modules.
Dimensions 118x170x7.5 cm



3639/1

COLUMN FOR 1-MODULE ENTRANCE PANEL, HEIGHT 170CM

Extruded aluminium column with steel coloured finish, aluminium rain shield and floor-mounted base, bolts provided. 1 module.
Dimensions 118x170x7.5 cm



3349

SIMPLEKEY MODULE WITH BLACK FACEPLATE

Module set up for use with Simplekey reader Art. SK9000I, SK9001I and SK9030I. Dimensions 112x89,5x22 mm.



33436

IKALL SIMPLEBUS/VIP 6 BUTTON MODULE

6-button IKALL entrance panel module for Simplebus/VIP system. Nameplate lighting options: blue/white/off. Dimensions 112x89.5x40 mm.



33434

IKALL SIMPLEBUS/VIP 4 BUTTON MODULE

4-button IKALL entrance panel module for Simplebus/VIP system. Nameplate lighting options: blue/white/off. Dimensions 112x89.5x40 mm.



33433

IKALL SIMPLEBUS/VIP 3 BUTTON MODULE

3-button IKALL entrance panel module for simplebus/VIP system. Nameplate lighting options: blue/white/off. Dimensions 112x89.5x40 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



33412

TWO-BUTTON AUDIO/VIDEO MODULE WITH BLACK FACEPLATE

Module designed for audio/video speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with a suitable video entry speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



33411

ONE-BUTTON VIDEO MODULE FOR IKALL ENTRANCE PANEL

Module designed for audio/video speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with a suitable video entry speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



33410

ZERO-BUTTON AUDIO/VIDEO MODULE WITH BLACK FACEPLATE

Module designed for audio/video speaker unit, with black screen-printed faceplate. To be fitted with a suitable video entry speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



33402

TWO-BUTTON AUDIO MODULE WITH BLACK FACEPLATE

Module designed for audio speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with an audio speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



33401

ONE-BUTTON AUDIO MODULE WITH BLACK FACEPLATE

Module designed for audio speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with an audio speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



33400

ZERO-BUTTON AUDIO MODULE WITH BLACK FACEPLATE

Module designed for audio speaker unit, with black screen-printed faceplate. To be fitted with an audio speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



3336

LIT MODULE. IKALL SERIES. SB SYSTEM

LED backlight module for various indications. Nameplate lighting options: blue/white/off. Contains card for writing names and user codes (max. 12). Dimensions 112x89,5x39 mm).



3334

PLAIN MODULE WITH BLACK FACEPLATE

Plain module with black faceplate. Dimensions 112x89.5x22 mm.



3313

VANDALPROOF SCREW KIT WITH KEY INCLUDED

KIT containing 2 tamper-proof screws for fixing the entrance panel finishing frame in place. Installation key included.



3311/4W

IKALL SERIES 4-MODULE HOLDER FRAME W/ WHITE FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 4 modules. White colour. Dimensions 125x395x37,5 mm



3311/4S

IKALL SERIES 4-MODULES HOLDER FRAME, SILVER FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 4 modules. Silver colour. Dimensions 125x395x37,5 mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3311/4A MODULE-HOLDER FRAME COMPLETE WITH FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 4 modules. Anthracite colour. Dimensions 125x395x37,5 mm



3311/3W IKALL SERIES 3-MODULE HOLDER FRAME W/ WHITE FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 3 modules. White colour. Dimensions 125x305x37,5 mm



3311/3A MODULE-HOLDER FRAME COMPLETE WITH FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 3 modules. Anthracite colour. Dimensions 125x305x37,5 mm



3311/2W IKALL SERIES 2-MODULE HOLDER FRAME W/ WHITE FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 2 modules. White colour. Dimensions 125x215x37,5mm



3311/2A MODULE-HOLDER FRAME COMPLETE WITH FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 2 modules. Anthracite colour. Dimensions 125x215x37,5mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3311/1W IKALL SERIES 1-MODULE HOLDER FRAME W/ WHITE FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 1 module. White colour. Dimensions 125x125x37,5mm



3311/1A MODULE-HOLDER FRAME COMPLETE WITH FINISHING FRAME

Made of die-cast aluminium and coated with special weather-resistant paint. 1 module. Anthracite colour. Dimensions 125x125x37,5mm



31169 IKALL HOUSING WITH RAINSHIELD 9 MODULE

Natural anodised aluminium housing with rain shield. 9 modules. Dimensions 408x332x85 mm



31166 IKALL HOUSING WITH RAINSHIELD 6 MODULE

Natural anodised aluminium housing with rain shield. 6 modules. Dimensions 281x332x44 mm



31164L IKALL HOUSING WITH RAINSHIELD 4 MODULE

Natural anodised aluminium housing with rain shield. 4 vertically-aligned modules. Dimensions 154x422x85 mm



31164 IKALL HOUSING WITH RAINSHIELD 4 MODULE

Natural anodised aluminium housing with rain shield. 4 modules. Dimensions 281x242x85 mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



31163

IKALL HOUSING WITH RAINSHIELD 3 MODULE

Natural anodised aluminium housing with rain shield. 3 modules.
Dimensions 154x332x85 mm



31162

IKALL HOUSING WITH RAINSHIELD 2 MODULE

Natural anodised aluminium housing with rain shield. 2 modules.
Dimensions 154x242x85 mm



31161

IKALL 1 MODULE HOUSING WITH RAINSHIELD

Natural anodised aluminium housing with rain shield. 1 module.
Dimensions 154x152x85 mm



31149

3X3 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 9 modules.
Dimensions 403x329x3 mm



31146

2X3 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 6 modules.
Dimensions 276x329x3 mm



31144L

4 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 4 vertically-aligned module. Dimensions 149x419x3 mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



31144

2X2 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 4 modules.
Dimensions 276x239x3 mm



31143

3 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 3 modules.
Dimensions 149x329x3 mm



31142

2 MODULES FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 2 modules.
Dimensions 149x239x3 mm



31141

1 MODULE FINISHING FRAME FOR ENTRANCE PANEL

Natural anodised aluminium finishing frame. 1 module. Dimensions
149x149x3 mm



31129

IKALL RAIN SHIELD FOR 9 MODULES

Natural anodised aluminium rain shield. 9 modules. Dimensions
408x332x44 mm



31126

IKALL RAIN SHIELD FOR 6 MODULES

Natural anodised aluminium rain shield. 6 modules. Dimensions
281x332x44 mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



31124L

IKALL RAIN SHIELD FOR 4 VERTICAL MODULES

Natural anodised aluminium rain shield. 4 vertically-aligned modules. Dimensions 154x422x44 mm



31124

RAIN SHIELD FOR 4 MODULE ENTRANCE PANEL

Natural anodised aluminium rain shield. 4 modules. Dimensions 281x242x44 mm



31123

RAIN SHIELD FOR 3 MODULE ENTRANCE PANEL

Natural anodised aluminium rain shield. 3 modules. Dimensions 154x332x44 mm



31122

RAIN SHIELD FOR 2 MODULE ENTRANCE PANEL

Natural anodised aluminium rain shield. 2 modules. Dimensions 154x242x44 mm



31121

RAIN SHIELD FOR 1 MODULE ENTRANCE PANEL

Natural anodised aluminum rain shield for 1 module Ikall panel. Dimensions 154x152x44 mm



3110/4

4 MODULES FLUSH-MOUNT BOX FOR ENTRANCE PANEL

Module-holder frame with finishing frame. 4 modules. Dimensions 118x387x45 mm



IKALL

MODULAR IKALL ENTRANCE PANEL

ACCESSORIES



3110/3

3 MODULES FLUSH-MOUNT BOX FOR ENTRANCE PANEL

Module-holder frame with finishing frame. 3 modules. Dimensions 118x297x45 mm



3110/2

2 MODULES FLUSH-MOUNT BOX FOR ENTRANCE PANEL

Module-holder frame with finishing frame. 2 modules. Dimensions 118x207x45 mm



3110/1

1 MODULE FLUSH-MOUNTED BOX FOR ENTRANCE PANEL

Module-holder frame with finishing frame. 1 module. Dimensions 118x118x45 mm



1622VC

2 WIRES IKALL AUDIO UNIT FOR REMOTE CAMERA

Module which allows modulation and transmission of the colour video signal on the riser. On input it has the composite video signal of a colour camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.

**IKALL****MODULAR IKALL ENTRANCE PANEL****ACCESSORIES****1622****IKALL SIMPLEBUS AUDIO SPEAKER**

Audio speaker unit for Simplebus system, complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming user calls. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus a 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.

**1595****120-230VAC / 33VDC POWER SUPPLY UNIT**

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).