



SWITCH

BRUSHED STAINLESS STEEL ENTRANCE PANEL



Switch featuring a minimalist and attractive style to complement modern architecture, the monolithic entrance panel is a single product encapsulating all the requirements and options of a simple and flexible set-up. Designed in Italy and made using brushed AISI 316 stainless steel for durability and resistance, the Switch entrance panel allows you to create an almost infinite range of solutions. The same front cover is used for digital 2-wire systems and ViP systems alike. In fact, the audio or audio/video module is sold separately; it is particularly interesting to note how an audio entrance panel can be converted into an audio/video panel by replacing the module itself and the front grille (supplied with the product for both solutions). The 2.5 mm thick plate is one of the thinnest available in this entire category and all the inserts are almost level, to create the ultimate balance while retaining the convenience of the removable nameplates on the front cover. The Switch entrance panel may be equipped with accessories that can be adapted with additional modules, such as keyless access systems (SimpleKey), induction circuits (T-Coil) or blank additional panels to be engraved with apartment names or street numbers. Comes complete with pre-fitted, pre-wired smart buttons designed and manufactured in-house. Protection rating IK08, voice messages and red LED light indications. Nameplates with white LED backlighting.



SWITCH

BRUSHED STAINLESS STEEL ENTRANCE PANEL

AWARDS

DESIGN
MILANO



SWITCH

BRUSHED STAINLESS STEEL ENTRANCE PANEL

GENERAL DATA

Depth (mm)	2.5
Product color	Steel
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.1621, Art.1622, Art.1622VC, Art.4680C, Art.4681
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Backlight colour	White

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III